



The Ingersoll Rand 236-SK Impactool offers professional technicians performance, comfort and durability with great value for money.

- 610 Nm (450 ft-lb) of maximum torque in reverse.
- The Ingersoll Rand impact mechanism with proprietary advanced metallurgy provides the ultimate in durability and reliability.
- Pressure-feed lubrication system automatically greases the impact mechanism for increased durability and reliability.
- Steel hammercase provides excellent durability under the toughest use.
- Feather-touch trigger allows precise delivery of power and speed.
- 2-position power regulator and forward/reverse control.
- Silenced through-handle exhaust reduces the noise level.
- Kit contains:
 - Impactool™,
 - 1/2" impact socket set (10 pcs) (10, 11, 12, 13, 14, 17, 19, 21, 22 and 24 mm).

Specifications at 6.2 bar (90 psi)

Part Number	236-SK
Ordering number	17020843
Drive size (square)	1/2 in
Other available versions:	
- bare tool	236

PERFORMANCE

Working torque in forward	25 - 200 ft-lb / 34 - 271 Nm
Maximum torque in forward	450 ft-lb / 610 Nm
Working torque in reverse	25 - 200 ft-lb / 34 - 271 Nm
Maximum torque in reverse	450 ft-lb / 610 Nm
Recommended fastener size	9/16 in / M14
Free speed	7 400 rpm
Impacts per minute	1 200

AIR SYSTEM

Air Inlet (NPT)	1/4 in
Minimum hose size	3/8 in / 10 mm
Average air consumption	4.3 CFM / 122 L/min
Air consumption at load	24.0 CFM / 680 L/min

NOISE & VIBRATION

Sound pressure / power (ISO15744)	90.3 / 101.3 dB(A)
Vibration level / measurement uncertainty (ISO28927)	12.0 / 1.0 m/s²

WEIGHT & DIMENSIONS

Tool weight	5.30 lb / 2.40 kg
Tool length	7.09 in / 180 mm
Shipping weight	6.00 lb / 4.45 kg
Shipping dimensions (L x W x H)	343 x 320 x 108 mm
UPC / EAN code	6 63023 06538 0
Origin	Made in China





SK4M3L
81287377
1/2" Impact socket set (3 pcs) (17, 19 and 21 mm)



SK4M14
81287351
1/2" Impact socket set (14 pcs) (10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 23 and 24 mm)



Impact sockets
For the complete range, see our accessory catalogue.



236-BOOT
45528148
Protective tool boot



33104
91486330
Hose whip, 1/4" NPT, 6 mm inside diameter, 30 cm (1 ft)



77NMC2
88104070
7N7/7S7 Series nipple, 1/4" male thread, 7.2 mm bore (EURO 7.2 - 7.4)



Filters, regulators, lubricators
For the complete range, see our accessory catalogue.



105-LBK1
04616090
Lubricant kit for Impacttools™ with metal housing



105-4T-6
04618930
Grease for Impacttools hammer mechanism (6 tubes)



236-TK1
80211618
Motor service kit



SK4M5L
81287369
1/2" Impact socket set (5 pcs) (17, 19, 21, 22 and 24 mm)



SK4M18
81287385
1/2" Impact socket set (18 pcs) (10, 11, 13, 14, 17, 19, 21, 22, 24, 13L, 14L, 21L, 24L, 17L, 19L and 21L mm, extension 125 mm)



4UA9
03070216
1/2" right-angle head (speed reduction: 25% torque output reduction: up to 50%)



IB6NMC2
88103015
IBN/IBS Series nipple, 1/4" male thread, 6 mm bore (ISO6150B / MIL-C4109)



Quick Release Couplings
For the complete range, see our accessory catalogue.



10Z4
03875671
Oil, Class 1, no. 10, 0.12 L



Lubricants
For the complete range, see our accessory catalogue.