

Air Drills, Screwdrivers and Specialty Tools



**7804XPA**  
Standard chuck, reversible



- 6.5 mm (1/4 in)
- 0.12 kW (0.17 HP)
- 1,600 rpm
- Only 0.8 kg and 180 mm
- Composite housing
- Reversible

Available in kits  
**7804KA** Standard chuck, reversible  
CCN: 47520772001



Includes 22-piece drill bit and driver set

Ref.	CCN	<div>SIZE</div> <div>mm</div>	<div>kWatt</div> <div>kW</div>	<div>1 min.</div> <div>rpm</div>	<div>kg</div>	<div>L</div> <div>mm</div>	<div>in</div>	<div>mm</div>	<div>l/s</div>	<div>MAX.</div> <div>l/s</div>	<div>dB(A)</div>	<div>m/s<sup>2</sup>/K<sup>(1)</sup></div>
7804XPA	47520751001	10	0.19	1,875	0.80	193	1/4 NPT	10	0.9	7.65	84.3	2.9/0.8

<sup>(1)</sup> ISO28927 – 3-axis measurement: vibration level/measurement uncertainty.

Air Drills, Screwdrivers and Specialty Tools | Drills

**7803A**  
Standard chuck



- 13 mm (1/2 in) chuck
- 0.37 kW (0.50 HP)
- 500 rpm

Also available  
**7803AKC**  
Keyless chuck  
**7803RA**  
Standard chuck, reversible  
**7803RAKC**  
Keyless chuck, reversible

Protection Boot  
**7803-BOOT**  
CCN: 45524287

**7802A**  
Standard chuck



- 10 mm (3/8 in) chuck
- 0.37 kW (0.50 HP)
- 2,000 rpm

Also available  
**7802AKC**  
Keyless chuck  
**7802RA**  
Standard chuck, reversible  
**7802RAKC**  
Keyless chuck, reversible

Protection Boot  
**7802-BOOT**  
CCN: 45524279

**7807R-EU**  
Standard chuck, reversible



- 10 mm (3/8 in) standard chuck
- 0.25 kW (0.33 HP)
- 2,000 rpm
- Reversible

**LA410-EU**  
Standard chuck



- 10 mm (3/8 in) standard chuck
- 0.25 kW (0.33 HP)
- 4,500 rpm

Ref.	CCN	<div>SIZE</div> <div>mm</div>	<div>kWatt</div> <div>kW</div>	<div>1 min.</div> <div>rpm</div>	<div>kg</div>	<div>L</div> <div>mm</div>	<div>in</div>	<div>mm</div>	<div>l/s</div>	<div>MAX.</div> <div>l/s</div>	<div>dB(A)</div>	<div>m/s<sup>2</sup>/K<sup>(1)</sup></div>
7803A	80113632	13	0.37	500	1.63	195	1/4 NPT	10	1.9	12.70	83.0	<2.5
7803AKC	10563724	13	0.37	500	1.63	200	1/4 NPT	10	1.9	12.70	83.0	<2.5
7803RA	80113673	13	0.37	500	1.64	195	1/4 NPT	10	1.9	12.70	83.0	<2.5
7803RAKC	10563732	13	0.37	500	1.64	200	1/4 NPT	10	1.9	12.70	83.0	<2.5
7802A	80113616	10	0.37	2,000	1.31	163	1/4 NPT	10	1.9	12.30	83.0	2.8/0.7
7807R-EU	01352160	10	0.25	1,800	1.07	206	1/4 NPT	10	1.9	8.10	89.2	<2.5
7802AKC	10563716	10	0.37	2,000	1.35	175	1/4 NPT	10	1.9	12.30	83.0	2.8/0.7
7802RA	80113640	10	0.37	2,000	1.30	163	1/4 NPT	10	1.9	12.30	83.0	2.8/0.7
7802RAKC	80147424	10	0.37	2,000	1.36	175	1/4 NPT	10	1.9	12.30	83.0	2.8/0.7
LA410-EU	01328616	10	0.25	4,500	0.91	228	1/4 NPT	10	1.4	12.80	84.9	2.9/0.7

<sup>(1)</sup> ISO28927 – 3-axis measurement: vibration level/measurement uncertainty.