


**Air pulse Nutrunners / Screwdrivers**  
**Clés hydro-pneumatiques**  
**Impulsschrauber**  
**Aprieturcas y atornilladores de impulso**  
**Chiavi ad impulso idraulico e cacciaviti**

**Power  
Pulse**



**Standard  
Equipment**

**Torque  
adjusting  
wrench**

**Vertical hanger  
on models  
100, 180, 280  
and 380**

Clé de réglage  
de couple

Suspension  
verticale sur  
modèles 100,  
180, 280 et  
380

Drehmoment-  
Einstellschlüssel

Vertikal-  
Aufhänger für  
Modelle 100,  
180, 280 und  
380

Llave para  
ajustar el par

Suspensión  
vertical para  
modelos  
100, 180,  
280 y 380

Chiave per  
regolazione  
della coppia

Dispositivo  
sospensione  
verticale per  
modelli 100,  
180, 280 y 380



See our Qualifier for pneumatic tools page 52  
 Voir notre Boîtier d'Assistance Qualité  
 pour outils pneumatiques page 52  
 Qualifikator für Druckluftwerkzeuge, Seite 52  
 Ver nuestro Cualificador de Procesos  
 para Herramientas Neumáticas página 52  
 Vedere il nostro Qualificatore di Processo  
 per Utensili Pneumatici pag. 52

Specifications at 90 psi – Caractéristiques à 620 kPa – Technische Daten bezogen auf 620 kPa  
 Especificaciones a 620 kPa – Caratteristiche a 620 kPa

3



180SQ1-EU



280P-EU



700P-EU






















**Non shut-off models**

**Modèles sans coupure d'air automatique**

**Modelle ohne Abschaltventil**

**Modelos sin parada automática**

**Modelli senza valvola di blocco**

Ref.	 Nm	 1 min. rpm	 kg	 mm	 mm	 in	 l/min
<b>IR PISTOL GRIP — POIGNÉE RÉVOLVER — PISTOLENGRIFF — EMPUÑADURA DE PISTOLA — IMPUGNATURA A PISTOLA</b>							
100PQ1-EU	4 - 11	9 500	0.70	142	18	1/4" 	220
180PQ1-EU	18 - 30	10 500	1.00	165	23	1/4" 	250
280P-EU	25 - 38	10 500	1.10	178	23	3/8" 	310
380P-EU	34 - 47	10 000	1.30	178	25	3/8" 	310
500P-EU	31 - 55	8 200	1.40	165	31	3/8" 	340
700P-EU	45 - 78	8 000	1.60	165	31	3/8" 	390
900P-EU	70 - 111	6 500	2.10	201	33	1/2" 	390
1100P-EU	85 - 123	4 700	2.20	208	36	1/2" 	450
<b>IR STRAIGHT HANDLE — POIGNÉE DROITE — GERADE AUSFUHRUNG — EMPUÑADURA RECTA — IMPUGNATURA DIRITTA</b>							
100SQ1-EU	6 - 12	9 500	0.80	226	21	1/4" 	250
180SQ1-EU	18 - 30	10 500	0.90	221	23	1/4" 	250
280SQ1-EU	20 - 34	10 500	0.90	229	23	1/4" 	310
380SQ1-EU	29 - 44	10 000	1.20	231	25	1/4" 	310
<b>IR ANGLE HEAD — A RENVOI D'ANGLE — WINKELKOPF — CABEZA ANGULAR — TESTA AD ANGOLO</b>							
500A-EU	30 - 45	7 500	1.50	267	28	3/8" 	340
700A-EU	36 - 50	5 000	2.00	284	28	3/8" 	340

Series /  
Baureihe



100P → 1100P

76 → 78 dBa

1/4" NPT

10 mm