

## 1/4" hex Cordless Impact Driver, 240 Nm (175 lb-ft)



**Convenience of Cordless. Power of Air.** The Ingersoll Rand W5111 20V Impactool delivers the power you need where you need it — from maintenance and repair operation to non-precision assembly. Designed for industrial use, the W5111 offers exceptional performance in a variety of applications. Experience the exceptional performance, versatility and durability of our W5111. The best-in-class power-to-weight ratio for access to tight spots, you can rely on the W5111 Impactool to do the job, do it fast, and do it every time.

- All-metal impact mechanism and drive train provide the ultimate in durability and reliability.
- Engineered composite housing for increased protection against chemical attack.
- Steel-reinforced housings add strength for unmatched drop resistance.
- Over-molded soft-touch grip minimizes vibration, reduces fatigue and enhances user comfort.
- Variable speed switch with electronic brake provides maximum control of the tool.
- Convenient one-hand operation with reverse control at trigger.
- Compatible with high-capacity 5.0 and 3.0 Ah batteries for maximum runtime or compact 2.5 Ah battery for reduced tool weight.
- Tool only is delivered without battery and charger. Kit contains: cordless tool, charger, 2 pcs 20 V, 2.5 Ah Li-ion batteries and blow molded case.

## Specifications

Part Number	W5111
Ordering number (tool only)	48620793
Part Number (kit)	W5111-K22-EU
Ordering number (kit)	47530971001
Voltage (DC)	20 V
Bit holder size (hex.)	1/4 in
Other available versions:	
- 3/8" square drive	W5131P
- 1/2" square drive	W5151P

## PERFORMANCE

Working torque with BL2005 battery	25 - 120 ft-lb / 35 - 160 Nm
Working torque with BL2010 battery	25 - 130 ft-lb / 35 - 175 Nm
Working torque in forward	25 - 120 ft-lb / 35 - 175 Nm
Maximum torque in forward	175 ft-lb / 240 Nm
Working torque in reverse	25 - 120 ft-lb / 35 - 175 Nm
Maximum torque in reverse	175 ft-lb / 240 Nm
Free speed	0 - 1 900 rpm
Impacts per minute	2 800

## NOISE & VIBRATION

Sound pressure / power (EN60745)	86.0 / 97.0 dB(A)
Vibration level / measurement uncertainty (EN60745)	4.7 / 1.2 m/s <sup>2</sup>

## WEIGHT & DIMENSIONS

Tool weight with BL2012 battery	3.60 lb / 1.60 kg
Tool weight with BL2010/BL2022 battery	4.20 lb / 1.90 kg
Tool length	6.1 in / 154 mm
Shipping weight (tool only)	3.50 lb / 1.59 kg
Shipping weight (kit)	11.30 lb / 5.10 kg
Shipping dimensions (tool only) (L x W x H)	216 x 216 x 89 mm
Shipping dimensions (kit) (L x W x H)	470 x 390 x 130 mm
UPC / EAN code (tool only)	6 63024 006252
UPC / EAN code (kit 2.5 Ah)	6 63024 006566
Origin	Made in China





**W5000-CASE**  
48622104  
Carrying case



**W5111-BOOT**  
47499747001  
Protective tool boot



**BL2005-BOOT**  
47510965001  
Protective battery boot BL2005/  
BL2012



**BL2010-BOOT**  
47510964001  
Protective battery boot BL2010/  
BL2022



**BL2010**  
48386791  
Li-Ion battery, 20 V, 3.0 Ah



**BL2012**  
47515903001  
Li-Ion battery, 20 V, 2.5 Ah



**BL2022**  
47515902001  
Li-Ion battery, 20 V, 5.0 Ah



**BC1121-EU**  
47507874001  
Universal battery charger 12/20V



**L5110**  
48489561  
Task light (without battery)



**67-4T**  
04637336  
Grease for high-speed angle heads



**70 1 LB**  
03364619  
No. 70 Grease, 0.45 kg



**105-4T-6**  
04618930  
Grease for Impacttools hammer  
mechanism (6 tubes)