



The Ingersoll Rand 2135QXPA Series Impactool™ was built on the hardworking and respected foundation laid by the 2135TiMAX. The result is a light, quiet and powerful impact wrench that delivers an incredible level of performance and power at a cost that won't punish your wallet. The 2135QXPA is the finely tuned and finely crafted impact wrench you need to tackle the toughest jobs.

- 1 057 Nm (780 ft-lb) of maximum torque in reverse.
- Ingersoll Rand TwinHammer impact mechanism is the strongest, most durable and longest life mechanism in the industry.
- Unique reverse-bias 7-vane motor delivers even more power in reverse.
- Ergonomic composite housing is lightweight, protects from cold air and offers great operator comfort.
- Feather-touch trigger allows precise delivery of power and speed.
- 4-position power regulator in forward helps adjusting the power to the application.
- One-hand forward/reverse switch for easy operation.
- 360° swivel inlet helps eliminating twisted hoses.
- Patented technology reduces the noise level without sacrificing the power.
- Optional piped-away exhaust system can further reduce noise level and directs air away from the operator.

## Specifications at 6.2 bar (90 psi)

Part Number	2135QXPA-2
Ordering number	47517914001
Drive size (square)	1/2 in
Torque settings (forward / reverse)	4 / 1
Other available versions:	

### PERFORMANCE

Maximum torque in forward	700 ft-lb / 949 Nm
Maximum torque in reverse	780 ft-lb / 1 057 Nm
Recommended fastener size	M14 in / 9/16
Free speed	11 000 rpm
Impacts per minute	1 250

### AIR SYSTEM

Air Inlet (NPT)	1/4 in
Minimum hose size	3/8 in / 10 mm
Average air consumption	5.8 CFM / 164 L/min
Air consumption at load	23.0 CFM / 651 L/min
Impacting sound pressure / power (ISO15744)	90.7 / 101.7 dB(A)
Free speed sound pressure / power (ISO15744)	86.0 / 97.0 dB(A)
Vibration level / measurement uncertainty (ISO28927)	9.7 / 1.8 m/s²

### WEIGHT & DIMENSIONS

Tool weight	4.3 lb / 1.90 kg
Tool dimensions (L x W x H)	241 x 69 x 182 mm
Shipping weight	5.0 lb / 2.3 kg
Shipping dimensions (L x W x H)	201 x 265 x 84 mm
UPC / EAN code	6 63023 120119
Origin	Assembled in the USA



# 2135QXPA-2

## ACCESSORIES



### SK4M3L

81287377

1/2" Impact socket set (3 pcs) (17, 19 and 21 mm)



### SK4M14

81287351

1/2" Impact socket set (14 pcs) (10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 23 and 24 mm)



### Impact sockets

For the complete range, see our accessory catalogue.

### 04706388

2131-366

Horizontal hanger



### SK4M5L

81287369

1/2" Impact socket set (5 pcs) (17, 19, 21, 22 and 24 mm)



### SK4M18

81287385

1/2" Impact socket set (18 pcs) (10, 11, 13, 14, 17, 19, 21, 22, 24, 13L, 14L, 21L, 24L, 17L, 19L and 21L mm, extension 125 mm)



### 4UA9

03070216

1/2" right-angle head  
(speed reduction: 25%  
torque output reduction: up to 50%)



### 2135-BOOT

45505377

Protective tool boot



### 2115-K284

45612637

Piped-away exhaust kit



### 33104

91486330

Hose whip, 1/4" NPT, 6 mm inside diameter, 30 cm (1 ft)



### 77NMC2

88104070

7N7/7S7 Series nipple, 1/4" male thread, 7.2 mm bore (EURO 7.2 - 7.4)



### IB6NMC2

88103015

IBN/IBS Series nipple, 1/4" male thread, 6 mm bore (ISO6150B / MIL-C4109)



### Quick Release Couplings

For the complete range, see our accessory catalogue.



### Filters, regulators, lubricators

For the complete range, see our accessory catalogue.



### 115-LBK1

04616108

Lubricant kit for Impacttools™ with composite housing



### 2135-THK1

80119571

Impact mechanism service kit



### 10Z4

03875671

Oil, Class 1, no. 10, 0.12 L



### 2135-TK2

45535028

Motor service kit